




TECHNICAL DATA SHEET

Type no.	600 26		
Article no.	010600260101		
Standards	DIN EN 50342-1, 50342-2		
Application	Starter battery		
Electrical data			
Rated voltage	12V		
Rated capacity	100 Ah (K20)		
Cold start current	600 A (EN)		
Dimensions and weights			
Box			
Length max.			413mm
Width max.			175mm
Box height max.			195mm
Total height max.			220mm
Battery weight	Ca. 29,5 kg (+/- 5 %)		
Electrolyte density	Approx. 1,28 kg/l		
Electrolyte	Diluted sulphuric acid		
Items/pallet	36		
Pallet ID	Euro pallet		
Items per layer	12		
Features			
Base hold-down	B00		
Layout	0		
Terminal	1		
Separator	PE bag separator		
Degassing	Battery with single degassing		
Flame arrester	Not integrated		
Maintenance 1)			
Water consumption	> 4g/Ah		
Refill water	Distilled or demineralised (DIN 43530)		
Self-discharge	Approx. 9 % per month		
Charging current	Approx. 1/10 of the rated capacity		
Charging voltage 2)	max. 13,8 V		

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

1 Document DBTBAT00339 prepared on 2015-07-01 ; Rights relating to changes and errors retained.
original